



North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 03/02/2009
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: PPG Industries, Inc.
Product Name: Extender

MATERIAL SAFETY DATA SHEET



SECTION 1 - PRODUCT AND COMPANY INFORMATION

Refinish Products
19699 Progress Drive
Strongsville, OH 44149

EMERGENCY PHONE NUMBERS (412) 434-4515 (U.S.)
(24 hours/day):

(514) 645-1320 (Canada)
01-800-00-21-400 (Mexico)
0532-3889090 (China)

TECHNICAL (440) 572-2800

INFORMATION:

PRODUCT SAFETY/MSDS INFORMATION: (412) 492-5555 7:00 a.m. - 4:30 p.m. EST

PRODUCT ID: DX87 (0808)

PRODUCT NAME: EXTENDER

SYNONYMS: None

ISSUE DATE: 01/20/2003

EDITION NO.: 1

CHEMICAL SOLVENT

FAMILY:

EMERGENCY OVERVIEW:

Flammable. Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke. Extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, and other sources of ignition during use and until all vapors/odors are gone. CAUSES EYE IRRITATION. MAY CAUSE SKIN BURNS. MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. VAPOR AND/OR SPRAY MIST HARMFUL IF INHALED. HARMFUL IF SWALLOWED.

SECTION 2 - COMPOSITION INFORMATION

The following ingredient(s) marked with an "x" are considered hazardous under applicable U.S. OSHA and/or Canadian WHMIS regulations. If no ingredients are listed, then there are no U.S. OSHA and/or Canadian WHMIS hazardous ingredients in this product.

<u>Material/ CAS Number</u>	<u>Percent</u>	<u>Hazardous</u>
ACETYLACETONE 123-54-6	60- 100	X

SECTION 3 - HAZARDS IDENTIFICATION

ACUTE OVEREXPOSURE EFFECTS

EYE CONTACT:

Causes eye irritation. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact.

SKIN CONTACT:

May cause skin burns. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

SKIN ABSORPTION:

May be harmful if absorbed through the skin.

INHALATION:

Vapor and/or spray mist harmful if inhaled.

INGESTION:

Harmful if swallowed.

SIGNS & SYMPTOMS OF OVEREXPOSURE:

Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Eye watering, headaches, nausea, dizziness and loss of coordination are indications that solvent levels are too high. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not applicable.

CHRONIC OVEREXPOSURE EFFECTS

Avoid long-term and repeated contact.

Repeated exposure to vapors above recommended exposure limits (see Section 8) may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

The effects of long-term, low level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the prevention of all contact with this material to avoid any effects from repetitive acute exposures. See Section 11, of this MSDS for a detailed list of chronic health effects information available on individual ingredients in this product.

SECTION 4 - FIRST AID MEASURES

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available.

EYE CONTACT:

Remove contact lens and pour a gentle stream of warm water through the affected eye for at least 15 minutes. If irritation persists, contact a poison control center, emergency room, or physician as further treatment may be necessary.

SKIN CONTACT:

Run a gentle stream of water over the affected area for 15 minutes. A mild soap may be used if available. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

INHALATION:

Remove from area to fresh air. If symptomatic, contact a poison control center, emergency room or physician for treatment information.

INGESTION:

Gently wipe or rinse the inside of the mouth with water. Sips of water may be given if person is fully conscious. Never give anything by mouth to an unconscious or convulsing person. Do Not induce vomiting. Contact a poison control center, emergency room or physician right away as further treatment will be necessary.

SECTION 5 - FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASHPOINT: 96 Degrees F (35 Degrees C)

FLASHPOINT TEST METHOD:

Pensky-Martens Closed Cup

UEL: Not Available.

LEL: Not Available.

AUTOIGNITION TEMPERATURE:

Not Available.

EXTINGUISHING MEDIA:

Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA Class IC flammable liquid fires. Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

PROTECTION OF FIREFIGHTERS:

Fire-fighters should wear self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Keep this product away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, static electricity). Invisible vapors can travel to a source of ignition and flash back. Do not smoke while using this product. Keep containers tightly closed when not in use. Closed containers may explode when overheated. Do not apply to hot surfaces. Toxic gases may form when this product comes in contact with extreme heat. May produce hazardous decomposition products when exposed to extreme heat. Extreme heat includes, but is not limited to, flame cutting, brazing, and welding.

SECTION 6 - ACCIDENTAL RELEASE MEASURE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Provide maximum ventilation. Only personnel equipped with proper respiratory, skin, and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sand, vermiculite, or other noncombustible absorbent material and place in clean, empty containers for disposal. Only the spilled material and the absorbant should be placed in this container.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING HANDLING AND STORAGE:

Vapors may collect in low areas. If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

STORAGE:

Do not store above 120 degrees F.(48 degrees C.). Store large quantities in buildings designed and protected for storage of NFPA Class IC flammable liquids.

SECTION 8 - EXPOSURE CONTROLS & PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 8 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

PERSONAL PROTECTIVE EQUIPMENT

EYES:

Wear safety glasses with side shields.

SKIN/GLOVES:

Wear protective clothing sufficient to cover exposed skin surfaces. For applications where skin contact is likely and impermeable clothing is necessary, select clothing constructed of: impermeable material. No specific permeation/degradation testing have been done on protective clothing for this product. Recommendations for skin protection are based on infrequent contact with this product. For frequent contact or total immersion, contact a manufacturer of protective clothing for appropriate chemical impervious equipment. Clean contaminated clothing and shoes.

RESPIRATOR:

Overexposure to vapors may be prevented by ensuring proper ventilation controls, vapor exhaust or fresh air entry. A NIOSH- approved air purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may also reduce exposure. Read the respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective, its limitations, and how it is to be properly fitted and used. Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, the LEL below the stated limit, and to remove decomposition products during welding or flame cutting.

GENERAL HYGIENE - ESTABLISHED EXPOSURE LIMITS

If Threshold Limit Values (TLVs) have been established by ACGIH, OSHA, Ontario or PPG, they will be listed below. These limits are

intended for use in the practice of industrial hygiene as guidelines or recommendations in the control of potential workplace health hazards. These limits are not a relative index of toxicity and should not be used by anyone without industrial hygiene training.

Key: OSHA=Occupational Safety and Health Administration; PEL=Permissible Exposure Limit; Ceiling=PEL Ceiling Limit; STEL=PEL Short-Term Exposure Limit; Skin=OSHA Skin Designation.

Material/ CAS Number	Percent	Ontario TWA	Ontario STEL	PPG IPEL	PPG STEL
ACETYLACETONE 123-54-6	60- 100	Not established	Not established	20 PPM	Not established

Key: ACGIH=American Conference of Governmental Industrial Hygienists; OSHA=Occupational Safety and Health Administration; TLV=Threshold Limit Value; TWA=Time Weighted Average; PEL=Permissible Exposure Limit; IPEL=Internal Permissible Exposure Limit; Ceiling=TLV or PEL Ceiling Limit; STEL=TLV or PEL Short-Term Exposure Limit; Skin= Skin Absorption Designation. [C- Ceiling Limit; S- Potential Skin Absorption; R-Respirable Dust]
Additional Information Not applicable.

SECTION 9 - PHYSICAL & CHEMICAL PROPERTIES

(FORMULA VALUES, NOT SALES SPECIFICATIONS)

SPECIFIC GRAVITY:	.977
PHYSICAL STATE:	Liquid
PERCENT SOLIDS:	.00
PERCENT VOLATILE BY VOLUME:	100.000
pH:	Not available.
ODOR THRESHOLD:	Not available.
VAPOUR PRESSURE (mm Hg):	Not Applicable.
ODOR/APPEARANCE:	Viscous liquid with an odor characteristic of the solvents listed in Section 2.
VAPOR DENSITY:	HEAVIER THAN AIR
EVAPORATION RATE:	75
BOILING POINT OR RANGE:	284 - 284Degrees F
FREEZING POINT OR RANGE:	Not Applicable.
MELTING POINT OR RANGE:	Not Applicable.
OCTANOL/WATER PARTITION COEFFICIENT:	Not Applicable.
WEIGHT PER GALLON:	8.14 (U.S.) / 9.7 (IMPERIAL)

SECTION 10 - STABILITY AND REACTIVITY

STABILITY:
This product is normally stable and will not undergo hazardous reactions.

CONDITIONS TO AVOID:
None Known.

INCOMPATIBLE MATERIALS:
Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

HAZARDOUS POLYMERIZATION:
None Known.

HAZARDOUS DECOMPOSITION PRODUCTS:
- Carbon dioxide

SECTION 11 - TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

**Refinish Products
19699 Progress Drive
Strongsville, OH 44149**

**PRODUCT ID: DX87 (0808)
PRODUCT NAME: EXTENDER**

Material/ CAS Number	Percent	ORAL LD50 (g/kg)	DERMAL LD50 (g/kg)	INHALATION LC50 (mg/l)
ACETYLACETONE 123-54-6	60- 100	.55 g/kg	.81 g/kg	Not Available

CHRONIC TOXICITY

TARGET ORGANS:

- Brain - Blood - Central nervous system - Lung

MUTAGENICITY:

This has not been tested for this product.

REPRODUCTIVE:

This has not been tested for this product.

SUPPLEMENTAL HEALTH INFORMATION:

Material/ CAS Number	Percent	Ingredient Specific Animal Data:
ACETYLAC ETONE 123-54-6	60- 100	This product contains 2,4-pentadione. Animals repeatedly inhaling high concentrations (up to 650 ppm) had the following toxic effects: decreased body weight, nasal lining thickening, anemia, brain/thymus degeneration and death (650 ppm level only). The low odor threshold, unpleasant odor and nauseating effects at levels of a few ppm should provide adequate warning to prevent overexposure in the workplace.

SECTION 12 - ECOLOGICAL INFORMATION

POTENTIAL ENVIRONMENTAL EFFECTS:

Ecotoxicity No data available

ENVIRONMENTAL FATE

MOBILITY: None Known.

BIODEGRADATION: None Known.

Bioaccumulation No data available

PHYSICAL/CHEMICAL

HYDROLYSIS: None Known.

PHOTOLYSIS: None Known.

SECTION 13 - DISPOSAL CONSIDERATIONS

Provide maximum ventilation, only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Take up spilled material with sawdust, vermiculite, or other absorbent material and place in containers for disposal.

Waste material must be disposed of in accordance with federal, state, provincial and local environmental control regulations. Empty containers should be recycled by an appropriately licensed reconditioner/salvager or disposed of through a permitted waste management facility. Additional disposal information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

SECTION 14 - TRANSPORTATION INFORMATION

Proper Shipping Name: Pentane-2,4-Dione
NOS Technical Name: None
Hazard Class: 3
Subsidiary Class(es): 6.1
UN Number: UN2310
Packing Group: III

USA - RQ Hazardous Substances: None

USA-RQ Hazardous Substance None

Threshold Ship Weight:

Marine Pollutant Name: None

SECTION 15 - REGULATORY INFORMATION

INVENTORY STATUS

U.S. TSCA: This product and/or all of its components are listed on the U.S. TSCA Inventory or is otherwise exempt from TSCA Inventory reporting requirements.

FEDERAL REGULATIONS

US Regulations

Material/ CAS Number	Percent	CERCLA HS - RQ (LBS)	SARA EHS- TPQ (LBS)	SARA 313
ACETYLACETONE 123-54-6	60- 100	Not Listed	Not Listed	Not Listed

SARA 311/312

Health (acute): Yes

Health (chronic): No

Fire (flammable): Yes

Pressure: No

Reactivity: No

WHMIS HAZARD CLASS: - Class B, Division 2 - Class D, Division 1, Subdivision B - Class D, Division 2, Subdivision B

STATE/PROVINCIAL REGULATIONS

Additional Information

Key: IARC- International Agency on the Research of Cancer; ACGIH- American Conference of Governmental Industrial Hygienists; NTP- National Toxicology Program *Denotes chemical as NTP Known Carcinogen; + Denotes NTP Possible Carcinogen; OSHA- Occupational Safety and Health Administration.

SECTION 16 - OTHER INFORMATION

Hazard Rating Systems

NFPA Rating: 3 30

HMIS Rating: 3 30

Rating System: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe, *=Chronic Effects.

HMIS=Hazardous Materials Identification System; NFPA=National Fire Protection Association;

Safe handling of this product requires that all of the information on the MSDS be evaluated for specific work environments and conditions of use.

PREPARED BY: Product Safety Department

REASON FOR REVISION: Date. Edition.

Updated MSDS

format.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200), the supplier notification requirements of SARA Title III, Section 313 and other applicable right-to-know regulations.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

DX87 000001 (00149148.016)(01/18/03)
990105, 000, 0808

*** END OF MSDS ***

**Refinish Products
19699 Progress Drive
Strongsville, OH 44149**

**PRODUCT ID: DX87 (0808)
PRODUCT NAME: EXTENDER**

16.6 % 3200 1 0808 DX87 F 000