



# MSDS MATERIAL SAFETY DATA SHEET

**HI-VALLEY CHEMICAL INC. \ LAB SUPPLY**  
 • 1134 WEST 850 NORTH CENTERVILLE, UTAH 84014 •  
 (801) 295-9591 • www.hvchemical.com

## Formalin, 10% Solution

### 1. === Product Identification ===

B>Synonyms: None

CAS No.: 50-00-0

Molecular Weight: Not applicable to mixtures.

Chemical Formula: Not applicable to mixtures.

### 2. === Composition/Information on Ingredients ===

Ingredient	CAS No	Percent	Hazardous
Formaldehyde	50-00-0	3 - 4%	Yes
Methyl Alcohol	67-56-1	1 - 1.5%	Yes
Water	7732-18-5	94 - 96%	No

### 3. === Hazards Identification ===

#### Emergency Overview

**DANGER! MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. STRONG SENSITIZER. MAY CAUSE BLINDNESS. COMBUSTIBLE LIQUID AND VAPOR. SUSPECT CANCER HAZARD. CONTAINS FORMALDEHYDE WHICH MAY CAUSE CANCER. Risk of cancer depends upon duration and level of exposure.**

**J.T. Baker SAF-T-DATA<sup>(tm)</sup> Ratings** (Provided here for your convenience)

Health Rating: 3 - Severe (Cancer Causing)

Flammability Rating: 0 - None

Reactivity Rating: 0 - None

Contact Rating: 2 - Moderate

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: Blue (Health)

#### Potential Health Effects

The perception of formaldehyde by odor and eye irritation becomes less sensitive with time as one adapts to formaldehyde. This can lead to overexposure if a worker is relying on formaldehyde's warning properties to alert him or her to the potential for exposure.

**Inhalation:**

May cause sore throat, coughing, and shortness of breath. Causes irritation and sensitization of the respiratory tract. Concentrations of 25 to 30 ppm cause severe respiratory tract injury leading to pulmonary edema and pneumonitis. May be fatal in high concentrations.

**Ingestion:**

Can cause severe abdominal pain, violent vomiting, headache, and diarrhea. Larger doses may produce decreased body temperature, pain in the digestive tract, shallow respiration, weak irregular pulse, unconsciousness and death. Methanol component affects the optic nerve and may cause blindness.

**Skin Contact:**

Toxic. May cause irritation to skin with redness, pain, and possibly burns. Skin absorption may occur with symptoms paralleling those from ingestion. Formaldehyde is a severe skin irritant and sensitizer. Contact causes white discoloration, smarting, cracking and scaling.

**Eye Contact:**

Vapors cause irritation to the eyes with redness, pain, and blurred vision. Higher concentrations or splashes may cause irreversible eye damage.

**Chronic Exposure:**

Frequent or prolonged exposure to formaldehyde may cause hypersensitivity leading to contact dermatitis. Repeated or prolonged skin contact with formaldehyde may cause an allergic reaction in some people. Vision impairment and enlargement of liver may occur from methanol component. Formaldehyde is a suspected carcinogen (positive animal inhalation studies).

**Aggravation of Pre-existing Conditions:**

Persons with pre-existing skin disorders or eye problems, or impaired liver, kidney or respiratory function may be more susceptible to the effects of the substance. Previously exposed persons may have an allergic reaction to future exposures.

---

**4. ===First Aid Measures ===**

**Inhalation:**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

**Ingestion:**

Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Skin Contact:**

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention immediately.

**Eye Contact:**

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

---

**5. === Fire Fighting Measures ===**

**Fire:**

Flash point: 85C (185F) CC

Combustible liquid and vapor! Gas vaporizes from solution and is flammable in air.

**Explosion:**

Above the flash point, explosive vapor-air mixtures may be formed. Containers may explode when involved in a fire.

**Fire Extinguishing Media:**

Water spray, dry chemical, alcohol foam, or carbon dioxide.

**Special Information:**

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode. Water spray may be used to keep fire exposed containers cool. Use water spray to blanket fire, cool fire exposed containers, and to flush non-ignited spills or vapors away from fire.

---

**6. === Accidental Release Measures ===**

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

---

**7. === Handling and Storage ===**

Store in a tightly closed container. Protect against physical damage. Outside or detached storage is preferred. Inside storage should be in a standard flammable liquids storage room or cabinet. Separate from oxidizing materials. Storage and use areas should be No Smoking areas. Wear special protective equipment (Sec. 8) for maintenance break-in or where exposures may exceed established exposure levels. Wash hands, face, forearms and neck when exiting restricted areas. Shower, dispose of outer clothing, change to clean garments at the end of the day. Avoid cross-contamination of street clothes. Wash hands before eating and do not eat, drink, or smoke in workplace. Protect from freezing. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product.

---

**8. === Exposure Controls /Personal Protection ===****Airborne Exposure Limits:**

-OSHA Permissible Exposure Limit (PEL):

0.75 ppm (TWA), 2 ppm (STEL), 0.5 ppm (TWA) action level for formaldehyde

200 ppm (TWA) for methanol

-ACGIH Threshold Limit Value (TLV):

0.3 ppm Ceiling formaldehyde, Sensitizer, A2 Suspected Human Carcinogen

200 ppm (TWA) 250 ppm (STEL) skin for methanol

**Ventilation System:**

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

**Personal Respirators (NIOSH Approved):**

If the exposure limit is exceeded and engineering controls are not feasible, a full facepiece respirator with a formaldehyde cartridge may be worn up to 50 times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. **WARNING:** Air purifying respirators do not protect workers in oxygen-deficient atmospheres. Irritation also provides warning. For Methanol: If the exposure limit is exceeded and engineering controls are not feasible, wear a supplied air, full-facepiece respirator, airlined hood, or full-facepiece self-contained breathing apparatus. Breathing air quality must meet the requirements of the OSHA respiratory protection standard (29CFR1910.134). Where respirators are required, you must have a written program covering the basic requirements in the OSHA respirator standard. These include

training, fit testing, medical approval, cleaning, maintenance, cartridge change schedules, etc. See 29CFR1910.134 for details.

**Skin Protection:**

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

**Eye Protection:**

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

**Other Control Measures:**

See OSHA Standard for more information on personal protective equipment, engineering and work practice controls, medical surveillance, record keeping, and reporting requirements. (29 CFR 1910.1048)

---

**9. === Physical/Chemical Properties ===**

**Appearance:**

Clear, colorless liquid.

**Odor:**

Pungent odor.

**Solubility:**

Complete (100%)

**Specific Gravity:**

1.09

**pH:**

No information found.

**% Volatiles by volume @ 21C (70F):**

100

**Boiling Point:**

ca. 100C (ca. 212F)

**Melting Point:**

ca. 0C (ca. 32F)

**Vapor Density (Air=1):**

Essentially the same as water.

**Vapor Pressure (mm Hg):**

Essentially the same as water.

**Evaporation Rate (BuAc=1):**

Essentially the same as water.

---

**10. === Stability and Reactivity Data ===**

**Stability:**

Stable under ordinary conditions of use and storage.

**Hazardous Decomposition Products:**

May form carbon dioxide, carbon monoxide, and formaldehyde when heated to decomposition.

**Hazardous Polymerization:**

Will not occur.

**Incompatibilities:**

Incompatible with oxidizing agents and alkalis. Reacts explosively with nitrogen dioxide at ca. 180C (356F). Reacts violently with perchloric acid, perchloric acid-aniline mixtures, and nitromethane. Reaction with hydrochloric acid may form bis-chloromethyl ether, an OSHA regulated carcinogen.

**Conditions to Avoid:**

Heat, flames, ignition sources and incompatibles.

---

**11. === Toxicological Information ===**

Formaldehyde: Oral rat LD50: 100 mg/kg; skin rabbit LD50: 270 uL/kg, Irritation data: eye, rabbit, 750ug Severe; inhalation rat LC50: 203 mg/m<sup>3</sup>; investigated as a tumorigen, mutagen, reproductive effector; Cancer Status: an OSHA regulated carcinogen. Methanol: oral rat LD50: 5628 mg/kg; inhalation rat LC50: 64000 ppm/4H; skin rabbit LD50: 15800 mg/kg; investigated as a tumorigen, mutagen, reproductive effector.

-----\Cancer Lists\-----			
Ingredient	---NTP Known	Carcinogen Anticipated	IARC Category
Formaldehyde (50-00-0)	No	Yes	2A
Methyl Alcohol (67-56-1)	No	No	None
Water (7732-18-5)	No	No	None

**12. === Ecological Information ===****Environmental Fate:**

The following statements refer to the environmental fate of formaldehyde. When released into the soil, this material is expected to leach into groundwater. When released into water, this material is expected to readily biodegrade. When released into water, this material is not expected to evaporate significantly. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to be readily degraded by photolysis. When released into the air, this material is expected to be readily removed from the atmosphere by dry and wet deposition. When released into the air, this material is expected to have a half-life of less than 1 day.

The following statements refer to the environmental fate of methanol. When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is expected to leach into groundwater. When released into the soil, this material is expected to quickly evaporate. When released into water, this material is expected to readily biodegrade. When released into the water, this material is expected to have a half-life between 1 and 10 days. When released into the air, this material is expected to exist in the aerosol phase with a short half-life. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to be readily removed from the atmosphere by wet deposition. When released into air, this material is expected to have a half-life between 10 and 30 days.

**Environmental Toxicity:**

The following toxicity information is for the formaldehyde portion. This material is expected to be slightly toxic to aquatic life. The LC50/96-hour values for fish are between 10 and 100 mg/l.

The methanol portion is expected to be slightly toxic to aquatic life. The LC50/96-hour values for fish are between 10 and 100 mg/l.

**13. === Disposal Considerations ===**

Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

**14. === MSDS Transport Information ===**

Not regulated.

**15. Regulatory Information**

-----\Chemical Inventory Status - Part 1\-----				
Ingredient	TSCA	EC	Japan	Australia
Formaldehyde (50-00-0)	Yes	Yes	Yes	Yes
Methyl Alcohol (67-56-1)	Yes	Yes	Yes	Yes
Water (7732-18-5)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----				
Ingredient	Korea	DSL	--Canada-- NDSL	Phil.
Formaldehyde (50-00-0)	Yes	Yes	No	Yes
Methyl Alcohol (67-56-1)	Yes	Yes	No	Yes
Water (7732-18-5)	Yes	Yes	No	Yes

-----\Federal, State & International Regulations - Part 1\-----				
Ingredient	-SARA 302-		-----SARA 313-----	
	RQ	TPQ	List	Chemical Catg.
Formaldehyde (50-00-0)	100	500	Yes	No
Methyl Alcohol (67-56-1)	No	No	Yes	No
Water (7732-18-5)	No	No	No	No

-----\Federal, State & International Regulations - Part 2\-----			
Ingredient	CERCLA	-RCRA-	-TSCA-
		261.33	8(d)
Formaldehyde (50-00-0)	100	U122	No
Methyl Alcohol (67-56-1)	5000	U154	No
Water (7732-18-5)	No	No	No

Chemical Weapons Convention: No      TSCA 12(b): No      CDTA: No  
 SARA 311/312: Acute: Yes      Chronic: Yes      Fire: Yes      Pressure: No  
 Reactivity: No      (Mixture / Liquid)

**WARNING:**

**THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.**

**Australian Hazchem Code:** None allocated.

**Poison Schedule:** None allocated.

**WHMIS:**

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**16. Other Information**

**NFPA Ratings:** Health: **2** Flammability: **2** Reactivity: **0**

**Label Hazard Warning:**

**DANGER! MAY BE FATAL IF SWALLOWED. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. CAUSES IRRITATION TO SKIN, EYES AND RESPIRATORY TRACT. STRONG SENSITIZER. MAY CAUSE BLINDNESS. COMBUSTIBLE LIQUID AND VAPOR. SUSPECT CANCER HAZARD. CONTAINS FORMALDEHYDE WHICH MAY CAUSE CANCER.** Risk of cancer depends upon duration and level of exposure.

**Label Precautions:**

Keep away from heat, sparks and flame.

Do not breathe vapor.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Do not get in eyes, on skin, or on clothing.

Physical and health hazard information is available from employer and from material safety data sheets.

**Label First Aid:**

If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. In all cases get medical attention immediately.

**Product Use:**

Laboratory Reagent.

---

*[High Valley Products, Inc.](#) provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.*

HIGH VALLEY PRODUCTS, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, HIGH VALLEY PRODUCTS, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Revision Date 1/2007